

SPECIFICATION FOR GRUBBING

320. 1. SCOPE

Grubbing shall consist of the removal and disposal of all stumps and roots and other debris.

320. 7. CONSTRUCTION METHODS

Stumps and roots located on areas designated or staked out by the Engineer shall be grubbed out. In general, these will be on excavation areas and on the embankment areas where the grade is less than one metre above the original ground level.

The disposal of roots, stumps and other debris, hereinafter referred to as debris, shall be as directed or permitted by the Engineer.

Grubbing shall be completed at least one kilometre in advance of grading operations. The Contractor shall not grub or burn without permission of the Engineer.

Debris, if possible, shall be piled and burned. The piling and burning operations shall be undertaken in such a manner and at locations that they will not interfere with the construction of the roadway and where burning of the debris will not damage live trees, pole lines, adjacent property or structures. The Contractor shall be liable for any damages occurring in the performance of this work.

Debris which cannot be burned, is to be buried in borrow pits or ditch sub-cuts. Where disposal is permitted or directed, the debris is to be levelled so that adequate earth covering can be spread over it.

Grubbing and burning operations shall be conducted in accordance with the applicable Provincial and Municipal regulations and Acts.

The Contractor shall take precautions to prevent fires from spreading and shall be liable for any damages occasioned in the performance of this work.

320. 9. METHOD OF MEASUREMENT

The number of hectares of "Grubbing" for which the Contractor will be paid will be derived from measurements made by the Engineer of the area staked out by him, and actually grubbed.

320. 11. BASIS OF PAYMENT

"Grubbing" will be paid for at the unit price per hectare set forth in the Contract for "Grubbing" which will be payment in full for performing all operations necessary or incidental thereto.